



User guideline for Power Dry desiccant package

<u>Note</u>: When you open the desiccant carton box to take out the desiccant packages to use, absolutely do not use knives, scissors, or sharp objects to open, because it is easy to cut too deep into the box, it causes tearing of the desiccant packages inside in the box.



Please instruct workers to put desiccant packages in the box as follows:

Let the surface of the desiccant pack with the word (THIS SIDE DOWN) in blue come in contact with the product, the white side without the letters facing up does not come into contact with the product, so when we open the box to check, we will see the white side, no letter of the desiccant package as shown below:



In case the desiccant packs are not used up: we can tie them up tightly for the next use, because in the cartons, each PE bag containing the desiccant packs has a string tied at the mouth of the PE bag.

Note: Unused desiccant packs must always be tightly tied in PE bags to absolutely prevent air from entering the bag.

Methods of preservation:

Place desiccants boxes on pallets in a cool, dry, water-free environment.

User manual for container

1. Make sure that the container is in good condition with no leaks or holes.



2. Measure the moisture content of container floor. There are 9 points to be checked on the 20ft container and 12 points on the 40ft container



3. Seal off all ventilations of the container

Usage proposal of container desiccant bags in a 20ft or 40ft container normally

4. Prepare container desiccant bags for placing inside the container, hang it on the container hook available inside the container. Below are the diagrams for placing 8 - 16 bags in 40ft container and 4 - 8 bags in 20ft container depending on moisture content as below:

Unit s container desiccant bags in various moisture content		
Moisture content %	20ft container	40ft container
Below 10	4	8
11 – 15	5	10
16 – 20	6	12
21 - 25	8	16
20 "		











Unload



Please contact us for further information:

Email: sales@lapphu.com Hotline: +84 907359061

User manual for small

Usage of small bags to place in boxes / cartons

Valuma of the box (m3)	Power Dry
Volume of the box (m ³)	Power-Dry
	(gr)
0.90 - 1.00	100
0.80 - 0.89	90
0.70 - 0.79	80
0.60 - 0.69	70
0.50 - 0.59	60
0.40 - 0.49	50
0.30 - 0.39	40
0.20 - 0.29	30
0.10 - 0.19	20
0.08 - 0.099	10
0.06 - 0.079	8
0.04 - 0.059	6
0.01 - 0.039	4

This guide is for reference only. The number of desiccant packages put in the box can vary depending on some factors such as: packaging methods, materials used for packaging, moisture content of goods, high or low seasons as well as % relative humidity (RH%) is high or low according to the time of shipment, time of transport of goods to the port of destination, the moisture inside the container, status and quality of containers etc

Please fasten the inner PE bag for next time use in case the desiccant box was opened but not used up.

For storage condition and shelf life: please keep desiccant cartons in cool, dry environment and be placed on the pallet, 24 months for storage without opening.









Please contact us for further information:

Email: sales@lapphu.com Hotline: +84 907359061